

**ELEVATION CERTIFICATE**  
**FEDERAL EMERGENCY MANAGEMENT AGENCY**  
**NATIONAL FLOOD INSURANCE PROGRAM**

D.M.B. No 3057-0077  
Expires May 31, 1993

ITION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to obtain elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

| SECTION A PROPERTY INFORMATION                                                                                       |  | FOR INSURANCE COMPANY USE |
|----------------------------------------------------------------------------------------------------------------------|--|---------------------------|
| NG OWNER'S NAME<br><b>MORGAN WALK DEVELOPMENT GROUP</b>                                                              |  | POLICY NUMBER             |
| ADDRESS (Including Apt., Unit, Suite and/or Building Number) OR P.O. ROUTE AND BOX NUMBER<br><b>10 The Crossings</b> |  | COMPANY NAIC NUMBER       |

(DESCRIPTION (Lot and Block Numbers, etc.)

**LOT 12, PARKSIDE****RICHMOND HILL**STATE  
**Georgia**ZIP CODE  
**31324****SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION**

Indicate the following from the proper FIRM (See Instructions):

| COMMUNITY NUMBER | 2. PANEL NUMBER | 3. SUFFIX | 4. DATE OF FIRM INDEX | 5. FIRM ZONE | 6. BASE FLOOD ELEVATION<br>(in AO 25% RL, 100 year depth) |
|------------------|-----------------|-----------|-----------------------|--------------|-----------------------------------------------------------|
| <b>130018</b>    | <b>1</b>        | <b>B</b>  | <b>4-17-89</b>        | <b>A1</b>    | <b>17.0</b>                                               |

Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE):  NGVD '29  Other (describe on back). Indicate the FIRM Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: **11.11.11.11 feet NGVD** (or other FIRM datum—see Section B, Item 7).

**SECTION C BUILDING ELEVATION INFORMATION**

Indicate the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level **11.11.11**.

FIRM Zones A1-A30, AE, AH, and A (without BFE). The top of the reference level floor from the selected diagram is at an elevation of **11.11.11.11** feet NGVD (or other FIRM datum—see Section B, Item 7).

FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of **11.11.11.11** feet NGVD (or other FIRM datum—see Section B, Item 7).

FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is **11.11.11** feet above  or below  (check one) the highest grade adjacent to the building.

FIRM Zone AO. The floor used as the reference level from the selected diagram is **11.11.11** feet above  or below  (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance?  Yes  No  Unknown

Indicate the elevation datum system used in determining the above reference level elevations:  NGVD '29  Other (describe in Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion in Comments on Page 2.)

Construction reference mark used appears on FIRM:  Yes  No (See Instructions on Page 4)

Reference level elevation is based on:  actual construction  construction drawings

NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)

Elevation of the lowest grade immediately adjacent to the building is: **11.11.11.11.11 feet NGVD** (or other FIRM datum—see Section B, Item 7).

**SECTION D COMMUNITY INFORMATION**

Community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: **11.11.11.11 feet NGVD** (or other FIRM datum—see Section B, Item 7).

Date of the start of construction or substantial improvement \_\_\_\_\_

**SECTION E CERTIFICATION .**


certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation certification when the elevation information for Zones A1-A30, AE, AH, A (with BFE), V1-V30, VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

ence level diagrams 6, 7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) noted in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

*I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.*

|                                                                                                                       |                                                             |                                |                     |
|-----------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|--------------------------------|---------------------|
| PIER'S NAME<br><u>J. M. Coleman</u>                                                                                   | LICENSE NUMBER (or Affix Seal)<br><u>GA R.L.S. No. 2486</u> |                                |                     |
| PROFESSION<br><u>C. Surveyor</u>                                                                                      | COMPANY NAME<br><u>EMC Engineering Services, Inc.</u>       |                                |                     |
| ADDRESS<br><u>East Charlton Street</u>                                                                                | CITY<br><u>Savannah</u>                                     | STATE<br><u>GA</u>             | ZIP<br><u>31401</u> |
| ATTACHED<br><u>Tank</u>                                                                                               | DATE<br><u>12/10/74</u>                                     | PHONE<br><u>(912) 232-6533</u> |                     |
| See should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner. |                                                             |                                |                     |

**MOVEMENTS:**



The diagrams above illustrate the points at which the elevations should be measured in A-Zones and V-Zones.

The diagram above illustrates the points to be measured for all 8 Zones should be measured at the top of the reference level floor.

Elevations for all A Zones should be measured at the top of the lowest horizontal structural member.  
Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.